

PFT1300

PoE Extender



Features

- Support passive PoE cascade power supply and Ethernet data exchange
- Support IEEE 802.3af/at standard power supply IP Camera
- Cooperate with High PoE Midspan (PFT1200), able to cascade level 2 PoE Extender, connect to 3 IPC (total power consumption $\leq 25W$), max transmission distance is 300m
- 1 * RJ45 10/100M PoE power supply port, supply power for IP Cam; 1 * RJ45 10/100M PoE power supply port, supply power for the next extender
- Installation mode: junction box mounting

Technical Specification

Model	PFT1300
Ethernet Port	1*10/100 Base-T PoE power receiving port 1*10/100 Base-T PoE power supply port, supply power for the next extender 1*10/100 Base-T PoE power supply port, supply power for IPC
Transmission Distance	Cooperate with DH-PFT1200, able to cascade level two extender, connect to 3 IPC (level one extender connects to 1 IPC, the OUT port of level two extender and CAMERA port connect to 1 IPC respectively, total power consumption $\leq 25W$), transmission distance is 300m
Power Consumption	$\leq 3W$
Application Humidity	10%~90%
Working Temperature	$0^{\circ}C \sim 65^{\circ}C$
Weight	5.7g
Dimension (WxDxH)	9mmx52mmx23mm

Application

